



We create chemistry

Distributed By:



Cleveland 1-800-362-9267

Canton 1-877-258-7601

Toledo 1-800-860-3352

www.chasehipps.com

Safety Data Sheet

MasterTop 200 neutral

Revision date : 2015/09/24

Version: 5.1

Page: 1/10

(30605580/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

MasterTop 200 neutral

Recommended use of the chemical and restriction on use

Recommended use*: for industrial and professional users

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF CORPORATION

100 Park Avenue

Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

CHEMTREC: 1-800-424-9300

BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Chemical family: No data available.

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Skin Corr./Irrit.

2

Skin corrosion/irritation

Eye Dam./Irrit.

1

Serious eye damage/eye irritation

STOT SE

3 (irritating to
respiratory system)

Specific target organ toxicity — single exposure

Aquatic Acute

3

Hazardous to the aquatic environment - acute

Label elements

Pictogram:

Safety Data Sheet

MasterTop 200 neutral

Revision date : 2015/09/24
Version: 5.1

Page: 2/10
(30605580/SDS_GEN_US/EN)



Signal Word:
Danger

Hazard Statement:

H318	Causes serious eye damage.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H402	Harmful to aquatic life.

Precautionary Statements (Prevention):

P280	Wear protective gloves and eye/face protection.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P260	Do not breathe dust/gas/mist/vapours.
P264	Wash with plenty of water and soap thoroughly after handling.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303 + P352	IF ON SKIN (or hair): Wash with plenty of soap and water.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash before reuse.

Precautionary Statements (Storage):

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

Precautionary Statements (Disposal):

P501	Dispose of contents/container to hazardous or special waste collection point.
------	---

Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Weight %</u>	<u>Chemical name</u>
65997-15-1	>= 25.0 - < 50.0%	Cement, portland, chemicals
13397-24-5	>= 0.3 - < 3.0%	Gypsum (Ca(SO ₄).2H ₂ O)
7632-00-0	>= 0.3 - < 1.0%	sodium nitrite
7440-44-0	>= 0.0 - < 5.0%	carbon
1317-65-3	>= 0.0 - < 3.0%	Limestone

Safety Data Sheet

MasterTop 200 neutral

Revision date : 2015/09/24
Version: 5.1

Page: 3/10
(30605580/SDS_GEN_US/EN)

4. First-Aid Measures

Description of first aid measures

General advice:

First aid personnel should pay attention to their own safety. Remove contaminated clothing.

If inhaled:

After inhalation of dust. Keep patient calm, remove to fresh air. If difficulties occur: Obtain medical attention.

If on skin:

After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:

Rinse mouth immediately and then drink plenty of water, seek medical attention. Do not induce vomiting unless told to by a poison control center or doctor.

Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Hazards: No applicable information available.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment:

Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:

foam, water spray, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons:

water jet

Additional information:

Product itself is non-combustible. Only the packaging materials can catch fire. The extinguishing agents normally used are sufficient.

Special hazards arising from the substance or mixture

Hazards during fire-fighting:

carbon monoxide, carbon dioxide, harmful vapours

Safety Data Sheet

MasterTop 200 neutral

Revision date : 2015/09/24
Version: 5.1

Page: 4/10
(30605580/SDS_GEN_US/EN)

Evolution of fumes/fog. The substances/groups of substances mentioned can be released in case of fire. Product is not combustible or explosive.

Advice for fire-fighters

Protective equipment for fire-fighting:

Wear self-contained breathing apparatus and chemical-protective clothing.

Further information:

Product itself is non-combustible; fire extinguishing method of surrounding areas must be considered. The degree of risk is governed by the burning substance and the fire conditions. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Avoid dust formation. Avoid contact with skin and eyes. Use personal protective clothing. Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions

Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

For small amounts: Pick up with suitable appliance and dispose of.

For large amounts: Pick up with suitable appliance and dispose of. Pack in tightly closed containers for disposal.

For residues: Rinse with plenty of water.

Avoid raising dust.

7. Handling and Storage

Precautions for safe handling

Avoid dust formation. The Cement contained in this product reacts alkaline when in contact with water or humidity. This may cause severe irritation of skin or mucous membranes. The humidity of the skin or mucous membranes is enough for this reaction. Prolonged direct contact to the dry product should be avoided therefore. Avoid inhalation of dusts. Avoid skin contact. Pour downwind and allow as little free fall as possible while emptying bags into equipment. Breathing must be protected when large quantities are decanted without local exhaust ventilation.

Protection against fire and explosion:

No special precautions necessary.

Conditions for safe storage, including any incompatibilities

Segregate from metals. Segregate from acids. Segregate from lyes. Segregate from oxidants. Segregate from foods and animal feeds.

Suitable materials for containers: High density polyethylene (HDPE)

Further information on storage conditions: Containers should be stored tightly sealed in a dry place.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

Safety Data Sheet

MasterTop 200 neutral

Revision date : 2015/09/24
Version: 5.1

Page: 5/10
(30605580/SDS_GEN_US/EN)

Limestone	OSHA PEL	PEL 5 mg/m3 Respirable fraction ; PEL 15 mg/m3 Total dust ; TWA value 15 mg/m3 Total dust ; TWA value 5 mg/m3 Respirable fraction ;
carbon	OSHA PEL	PEL 5 mg/m3 Respirable fraction ; PEL 15 mg/m3 Total dust ; TWA value 15 mg/m3 Total dust ; TWA value 5 mg/m3 Respirable fraction ; TWA value 50 millions of particles per cubic foot of air Total dust ; TWA value 15 millions of particles per cubic foot of air Respirable fraction ; TWA value 2.5 mg/m3 Respirable dust ; TWA value 10 mg/m3 Total dust ; TWA value 5 mg/m3 Respirable fraction ; TWA value 15 millions of particles per cubic foot of air ;
	ACGIH TLV	TWA value 2 mg/m3 Respirable fraction ; TWA value 10 mg/m3 Inhalable particles ; TWA value 3 mg/m3 Respirable particles ;
Gypsum (Ca(SO4).2H2O)	OSHA PEL	PEL 5 mg/m3 Respirable fraction ; PEL 15 mg/m3 Total dust ; TWA value 15 mg/m3 Total dust ; TWA value 5 mg/m3 Respirable fraction ;
	ACGIH TLV	TWA value 10 mg/m3 Inhalable fraction ;
Cement, portland, chemicals	OSHA PEL	PEL 15 mg/m3 Total dust ; PEL 5 mg/m3 Respirable fraction ;
	ACGIH TLV	TWA value 1 mg/m3 Respirable fraction ; The value is for particulate matter containing no asbestos and <1% crystalline silica.

Advice on system design:

Provide local exhaust ventilation to maintain recommended P.E.L.

Personal protective equipment

Respiratory protection:

Breathing protection if dusts are formed.

Hand protection:

Chemical resistant protective gloves, Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:

Tightly fitting safety goggles (chemical goggles).

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

Avoid contact with the skin, eyes and clothing. Avoid inhalation of dusts. In order to prevent contamination while handling, closed working clothes and working gloves should be used. Handle in accordance with good building materials hygiene and safety practice. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected

Safety Data Sheet

MasterTop 200 neutral

Revision date : 2015/09/24
Version: 5.1

Page: 6/10
(30605580/SDS_GEN_US/EN)

regularly and prior to each use. Replace if necessary (e.g. pinhole leaks). Contaminated equipment or clothing should be cleaned after each use or disposed of.

9. Physical and Chemical Properties

Form:	powder
Odour:	odourless
Odour threshold:	No applicable information available.
Colour:	grey
pH value:	approx. 12 - 13 (as aqueous suspension)
Melting temperature:	> 1,000 °C
boiling temperature:	not applicable
Sublimation temperature:	No applicable information available.
Flash point:	The substance/product is non-combustible.
Flammability:	not flammable
Lower explosion limit:	No applicable information available.
Upper explosion limit:	No applicable information available.
Autoignition:	No applicable information available.
Vapour pressure:	No applicable information available.
Relative density:	No applicable information available.
Bulk density:	approx. 1,800 - 2,400 kg/m ³
Vapour density:	No applicable information available.
Partitioning coefficient n-octanol/water (log Pow):	No applicable information available.
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.
Viscosity, dynamic:	No applicable information available.
Viscosity, kinematic:	No applicable information available.
Solubility in water:	(20 °C) dispersible
Miscibility with water:	(20 °C) not soluble
Solubility (quantitative):	No applicable information available.
Solubility (qualitative):	No applicable information available.
Evaporation rate:	No applicable information available.
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

The product is stable if stored and handled as prescribed/indicated.
Strong bases are formed on the addition of water.

Conditions to avoid

Avoid dust formation. Avoid humidity.

Safety Data Sheet

MasterTop 200 neutral

Revision date : 2015/09/24
Version: 5.1

Page: 7/10
(30605580/SDS_GEN_US/EN)

Incompatible materials

strong bases, strong acids

Hazardous decomposition products

Decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Virtually nontoxic after a single skin contact. Virtually nontoxic by inhalation. The product has not been tested. The statement has been derived from the properties of the individual components.

Oral

No applicable information available.

Inhalation

No applicable information available.

Dermal

No applicable information available.

Assessment other acute effects

Assessment of STOT single:

Causes temporary irritation of the respiratory tract.

The product has not been tested. The statement has been derived from the properties of the individual components.

Irritation / corrosion

Assessment of irritating effects: Risk of serious damage to eyes. Irritating to skin. Inhalation of particulates may cause respiratory tract irritation.

Sensitization

Assessment of sensitization: There is no evidence of a skin-sensitizing potential. The product has not been tested. The statement has been derived from the properties of the individual components. Chromate in this product has been reduced. Sensitization due to chromate within stated shelf-life is unlikely.

Chronic Toxicity/Effects

Repeated dose toxicity

Safety Data Sheet

MasterTop 200 neutral

Revision date : 2015/09/24
Version: 5.1

Page: 8/10
(30605580/SDS_GEN_US/EN)

Assessment of repeated dose toxicity: No reliable data was available concerning repeated dose toxicity. Based on available Data, the classification criteria are not met. The product has not been tested. The statement has been derived from the properties of the individual components.

Genetic toxicity

Assessment of mutagenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Reproductive toxicity

Assessment of reproduction toxicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Teratogenicity

Assessment of teratogenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Other Information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:
Acutely harmful for aquatic organisms.

Persistence and degradability

Assessment biodegradation and elimination (H₂O)

Inorganic product which cannot be eliminated from water by biological purification processes. The product is slightly soluble in water. It can be largely eliminated from the water by abiotic processes, e.g. mechanical separation.

Experience shows this product to be inert and non-degradable.

Elimination information

not applicable

Bioaccumulative potential

Assessment bioaccumulation potential

Safety Data Sheet

MasterTop 200 neutral

Revision date : 2015/09/24
Version: 5.1

Page: 9/10
(30605580/SDS_GEN_US/EN)

The product will not be readily bioavailable due to its consistency and insolubility in water.

Mobility in soil

Assessment transport between environmental compartments

The substance will not evaporate into the atmosphere from the water surface.

Following exposure to soil, adsorption to solid soil particles is probable, therefore contamination of groundwater is not expected.

Additional information

Other ecotoxicological advice:

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

13. Disposal considerations

Waste disposal of substance:

Dispose of in accordance with local authority regulations. Do not discharge into drains/surface waters/groundwater.

Container disposal:

Completely emptied packagings can be given for recycling.

14. Transport Information

Land transport

USDOT

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released; restriction on use / listed

This product contains an alkali metal nitrite which is subject to the SNUR at 40 CFR 721.4740 which prohibits the use of this product in metalworking fluids containing amines.
40 CFR 721.4740

EPCRA 311/312 (Hazard categories):

Acute; Chronic

Safety Data Sheet

MasterTop 200 neutral

Revision date : 2015/09/24
Version: 5.1

Page: 10/10
(30605580/SDS_GEN_US/EN)

<u>CERCLA RQ</u>	<u>CAS Number</u>	<u>Chemical name</u>
5000 LBS	7440-47-3; 7440-50-8	chromium; copper
100 LBS	7440-02-0; 7632-00-0	Nickel; sodium nitrite
10 LBS	7439-92-1	lead
1 LBS	7440-38-2	arsenic

CA Prop. 65:

WARNING: THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

NFPA Hazard codes:

Health : 3 Fire: 0 Reactivity: 0 Special:

16. Other Information

SDS Prepared by:

BASF NA Product Regulations
SDS Prepared on: 2015/09/24

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
END OF DATA SHEET

Distributed By:



Cleveland 1-800-362-9267
Canton 1-877-258-7601
Toledo 1-800-860-3352
www.chasehipps.com