



# BRICKFORM® Antique-It™

## Antiquing Agent

### PRODUCT DESCRIPTION

BRICKFORM Antique-It is a water soluble antiquing agent designed to impart a secondary color or highlight over stamped concrete or textured overlays. Antique-It is easy to apply, dries fast and provides a durable color that closely resembles the look of release powder.

### LIMITATIONS

When applying to existing concrete, the surface must be properly profiled. The slab must be open, porous, and absorptive to water. Be sure to reference preparation requirements for the sealer to be used to assure proper bonding.

### PACKAGING

BRICKFORM Antique-It comes in powder form and is packaged in a one gallon bucket.

### COVERAGE

BRICKFORM Antique-It will cover 1600-2000 square feet per 3 lb. container.

### COLORS

BRICKFORM Antique-It is available in all 40 standard colors.

### PREPARATION

Concrete surfaces must be cleaned and profiled to the recommended ICRI - CSP 1 - as specified in Guideline No. 310.2-2013 (formerly 03732), Selecting and Specifying Concrete Surface Preparation for Sealers, Coatings, and Polymer Overlays. The surface must be free of sealers, dirt, oil, paint, moss, dust and other contaminants and must be open and porous to accept the Antique-It. Proper and complete substrate preparation is critical to the success of the project. Surface preparation videos available at [www.brickform.com](http://www.brickform.com).

### APPLICATION

Pour one gallon of water into a five gallon pail, add 6 ounces of Antique-It powder and mix vigorously until all powder has dissolved. Pre-wet the slab to be treated. Dip a soft bristle brush in the Antique-It solution and agitate the product. Remove the brush and allow the solution to fall out of the brush and on to the slab. Move the product around to even the coverage and to allow the color to settle in the imprints. Continue the process of dipping the brush, agitating the mix and applying the product across the slab. Water can be sprayed on the product while it is still wet to dilute the color as needed. The ratio of water to powder can be increased or decreased depending on the desired intensity of the color.

BRICKFORM Antique-It can also be sprayed through a high quality pump up type sprayer. However, frequent and aggressive agitation is necessary to prevent clogs in the sprayer.

Average coverage rates for Antique-It will vary depending on the desired effects, texture, and porosity of the slab and range from a minimum of 200 square feet/gallon to 250 square feet/gallon.

**NOTE:** The Antique-It, once dry, may exhibit a white haze. Once sealed with an approved BRICKFORM sealer, this haze will disappear and the color will be significantly enhanced.

Please reference BRICKFORM Antique-It video at [www.brickform.com](http://www.brickform.com).

### SEALING

Allow Antique-It to completely dry prior to sealing. Drying times will vary with application rates and ambient conditions. Seal with BRICKFORM Gem-Seal, Poly-Seal, Poly-Astic, Decopoxy, or Uremax. Please consult the BRICKFORM TIS for any sealer used before using any of these sealers.

### MAINTENANCE

The sealed surface should be inspected periodically for areas of thin or traffic worn sealer and re-applied as needed. Please reference appropriate Technical Information Sheets for sealer to be used.

### WARRANTY

This product is not intended for public use and is intended for use by trained, professional contractors and installers. It is warranted to be of uniform quality, within manufacturing tolerances. The manufacturer has no control over the use of this product, therefore, no warranty, expressed or implied, is or can be made either as to the affects or as results of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing material proven to be defective. The end user shall be responsible for determining product's suitability and assumes all risks and liability.

BRICKFORM, A Division of Solomon Colors, Inc.  
4050 Color Plant Road  
Springfield, IL 62702

Toll Free 1-800-483-9628  
[www.brickform.com](http://www.brickform.com)