



TREMPRIME[™] SILICONE POROUS PRIMER

Single Component Silicone Primer for Porous Substrates



PRODUCT DESCRIPTION

TREMprime[™] Silicone Porous Primer is a single component primer used to enhance the adhesion of silicone sealants to porous surfaces such as concrete and limestone.

BASIC USES

TREMprime Silicone Porous Primer enhances the adhesion of silicone sealants to brick, concrete, precast, stone, EIFS, wood, and other porous surfaces.

FEATURES & BENEFITS

TREMprime Silicone Porous Primer requires no mixing and is easy to apply with a brush or clean cloth. TREMprime Silicone Porous Primer has a dry time of 30 to 45 minutes at 70 °F (21 °C). Silicone sealants can be applied up to 8 hr after primer has been applied.

AVAILABILITY

Readily available in 16 oz. bottles from your local Tremco Sales Representative, Tremco Distributor or Tremco Warehouse.

COLORS

Available in Clear.

LIMITATIONS

TREMprime Silicone Porous Primer must be completely dry before applying the silicone sealant. Addionally, if the sealant has not be applied after 8 hours, the surface must be cleaned with IPA and reprimed with TREMprime Silicone Porous Primer.

WARRANTY

A repair or replacement warranty is available on all Tremco products. Visit https://www.tremcosealants.com/warranties/ for details.

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

TPSPPDS/0822

Tremco Construction Products Group (CPG) brings together Tremco CPG Inc. and its Dryvit and Nudura brands; Willseal; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc. and its Pure Air Control Services and Canam Building Envelope Specialists offerings; and Weatherproofing Technologies Canada, Inc.



tremcosealants.com 800.321.7906



3735 Green Rd. | Beachwood, OH 44122 800.321.7906 | tremcocpg.com